Techsquare

ROOM STATIC PRESSURE CONTROLLER

Features

FULLY CALIBRATED AND TEMPERATURE COMPENSATED
OFFSET AND HYSTERESIS FREE
L.C.D 16X2 With Back light
NEGATIVE PRESSURE OPTIONAL
TWO TYPES CONTROL
a)RELAY OUTPUT
b)0-10V D.C.(PROPORTIONAL)

Applications

HVAC
CLEAN ROOM
PHARMACEUTICAL CLEAN ROOM
BIO-SAFTEY CLEAN ROOM
INDUSTRIAL
MEDICAL
ENERGY MANAGEMENT
PROCESS AUTOMATION

Dimension

Bezel Size 148X92
Panel Cutout 132X84



Specification

Operating Temperature - -40°C to +100°C
Input voltage- 12Volts to 15Volts A.C.
Operating Current - 100 m.A
Sensor Warm Up Time - 9 mSec to 50 mSec
Accuracy - 0.5 % FS
Range - 0 To 125 mm w c
Range For Negative- 0 To -5mm w c
RS- 485 Communication

Techsquare #41/5, No.8 1st Main,2nd Cross, Muthurayaswamy Layout, D.B.Sandra.
Vidhyaranyapura Post., Bangalore-560097Email Id :techsquare@gmail.com
Mobile:+91-8023455484,+91-99002-66937