Techsquare

STATIC PRESSURE INDICATOR

Features

Ratio Metric Output Versus Input
Differential Type
7-Segment Display 1 Inch
Negative Pressure Optional
Relay Optional
In-Build Buzzer
Four Functional Keys
2-Set Point Available
-Low Set Point
-High Set Point



Applications

Room Static Pressure Transmitter
Filter Static Pressure Transmitter
Clean Room Pressure indicator
Bio-Safety Cabinet
Laminar Flow Bench
AHU(Air Handling Unit)
Level Indicators
Leak Detectors

Dimension

Bezel Size	96X96
Panel Cutout	92X92
DEPTH	75mm

Specification

Operating Temperature - -40°C To +125°C
Input Voltage - 180V To 240V.A.C.
Operating Current - 100 m.A.
Sensor Warm Up Time - 10 mSec to 50 mSec
Accuracy - ±1.5 Vfss
Range - 0 mm H20 To 99 mm w c
Range For Negative- 0 To -15 mm w c
RS-485 Communication

Techsquare #41/5No.8 1st Main, 2nd Cross, Muthurayaswamy Layout D.B. Sandra
Vidhyaranyapura Post., Bangalore-560097 Email Id : techsquare@gmail.com
Mobile:+91-8023455484,+91-99002-66937